## IN THE SPECIFICATION:

Page 1, line 2, before the word "which" insert ∮now U.S. Patent No. 5,779,761--. al line 4, after "1994" insert -- (now abandoned)--; line 10, after "titanium" insert --,--; line 18, after "present" insert --,-Page 5, line 20, after "process" insert -:;--; line 21, delete "." and insert --; and-line 26, deleté "alkaline" first occurrence, and insért --alkali--. Page 7, line 13, after "thereof" insert ‡including a sodium pump 11--. Page 8, line 3, at the end of the sentence insert Preferably, the temperature of the sodium away from the location of halide introduction is maintained in the range of from about 200°C to about 400°C.--Page 10, line 11, after "process" insert -via a feed pump 21 and boiler 22--; line 13, delete "exchanger" and insert --exchangers 19 and--; line 16, after "chamber." insert 1-The recovered heat from heat exchangers 19 and 29 may be used to vaporize liquid ... line 20, delete "1." and insert --1,--. Page 11, line 4, after "of" insert --the--; line 8, delete the "," after the number "1"; line 10, after the word "problems" add -- with the prior art--; line 12, after the word "flow" insert --or injection--; Page 12, line 20, delete the "." after the number "2"; line 24, delete "being" and insert --was--.

73